



Door Description Tree (Page 2 of 2)

<u>Door Type</u>	
(D5) RS500 Aluminum Frame	(5B) RS500 Aluminum Frame Low Temp Oven
(D6) RS600 Aluminum Frame	(6B) RS600 Aluminum Frame Low Temp Oven
(5S) RS500 Stainless Frame	(5C) RS500 Aluminum Frame Intrinsic Barrier
(6S) RS600 Stainless Frame	(6C) RS600 Aluminum Frame Intrinsic Barrier
(5G) RS500 Galvanized Frame	(5E) RS500 Stainless Frame High Temp Oven
(6G) RS600 Galvanized Frame	(6E) RS600 Stainless Frame High Temp Oven
(1G) RS100 Galvanized Frame	(5F) RS500 Stainless Frame Low Temp Oven
(5H) RS500 Galvanized Frame High Temp Oven	(6F) RS600 Stainless Frame Low Temp Oven
(6H) RS600 Galvanized Frame High Temp Oven	(5J) RS500 Stainless Frame Intrinsic Barrier
(5L) RS500 Galvanized Frame Low Temp Oven	(6J) RS600 Stainless Frame Intrinsic Barrier
(6L) RS600 Galvanized Frame Low Temp Oven	(5K) RS500 WIC
(5I) RS500 Galvanized Frame Intrinsic Barrier	RS100 10' x 10' Max Size
(6I) RS600 Galvanized Frame Intrinsic Barrier	RS500 12' x 12' Max Size
(5A) RS500 Aluminum Frame High Temp Oven	RS600 24' x 24' Max Size
(6A) RS600 Aluminum Frame High Temp Oven	High Temp = 200° to 500° F
	Low Temp = < 200° F

<u>Mount Style</u>	
(A) Manaras D5 Front Left	(O) Chain Right
(B) Manaras D5 Front Right	(P) Chain Left
(C) Manaras D6 Front Left	(Q) Manaras D1 Right
(D) Manaras D6 Front Right	(R) Manaras D1 Left
(E) Manaras D5 Wall	(S) Somfy D1
(F) Manaras D6 Wall	(T) Manaras D5/6 Wall Right
(G) Chain D5	(U) Manaras D5/6 Wall Left
(H) Chain D6	(V) MFZ D6 Top Mount Right
(I) Brother D5 Left	(W) MFZ D6 Top Mount Left
(J) Brother D6 Left	(X) Manaras Top Left
(K) MFZ D5 Left	(Y) Manaras Top Right
(L) MFZ D5 Right	(Z) Brother D5 WIC
(M) MFZ D6 Left	
(N) MFZ D6 Right	

<u>Drive Type</u>	
(B10) Brother 1/4HP 15:1 325-V1 Standard	(MG5) Manaras Gearhead 1HP
(B20) Brother 1/2HP 10:1 650-V1 Standard	(MG1) Manaras Gearhead 1/2HP
<u>B20 Max Door Size 12'x12'</u>	(MPH) Manaras OPH 1/2 HP
(B30) Brother 1/2HP 15:1 650-V1 Standard	(MX5) Manaras OGHX Exp 1HP
(B40) Brother 1/2HP 15:1 650-V2 Standard	(MX1) Manaras OGHX Exp 1/2HP
(B50) Brother 1/2HP 12.5:1 650-V1 Standard	(MW1) Manaras OGHW Nem1/2HP
(B60) Brother 1/2HP 20:1 650-V1 Standard	(MFZ) MFZ Gearhead
(B61) Brother 1/2HP 20:1 650-V1 Plus	<u>M-Door Drive Type</u>
(B70) Brother 1/6hp 10:1 (GF18N010-BBYJ2C) WIC	(B1M) Brother 1/4HP 15:1 325M 115V (V1) Max 12x12
(B11) Brother 1/4HP 15:1 325-V1 Plus	(B2M) Brother 1/2HP 10:1 650M 230V (V1) Max 12W
(B21) Brother 1/2HP 10:1 650-V1 Plus	(B3M) Brother 1/2HP 15:1 650M 230V (V1) Max 17W
<u>B21 Max Door Size 12'x12'</u>	(B4M) Brother 1/4HP 15:1 325M 230V (V1) Max 12x12
(B31) Brother 1/2HP 15:1 650-V1 Plus	(B5M) Brother 1/2HP 10:1 650M 115V (V1) Max 8W
(B41) Brother 1/2HP 15:1 650-V2 Plus	(B6M) Brother 1/2HP 20:1 650M 230V (V1) Max 24W
(B51) Brother 1/2HP 12.5:1 650-V1 Plus	
(CHB) Chain Drive w/ Brake	
(CHN) Chain Drive	

<u>Materials List</u>	
(A) Anti Static	(N) Heavy Black 30 mil
(B) Frost	(O) Clear 10oz
(C) White	(P) Silver 10oz
(D) Orange	(Q) Yellow 26 Oz
(E) Black	(R) ACHT High Temp Panel 15 Mil
(F) Red	(S) 20 Mil Clear PVC
(G) Green	(T) Yellow / Black
(H) Blue	
(I) Tan	
(J) Yellow	
(K) Clear 7oz	
(L) Insulated	
(M) Heavy Blue 26 mil	